



ACR COPPER FITTINGS

Cambridge™ ACR copper fittings are rugged and highly resistant to corrosion. They are used as refrigerant lines in HVAC systems and to supply hot and cold water.

ACR 90° LONG TURN STREET ELBOWS



Spec:

FTG x C
90°

Made in compliance with ASME B16.22, NSF 61 and NSF372

| ITEM# | O.D. | I.D. | PSI -20°F to 100°F | PSI 150°F | PSI 200°F | PSI 250°F | PSI 300°F | PSI 350°F | PSI 400°F | PACK QTY | CASE QTY |
|--------|------|------|-----------------------|--------------|--------------|--------------|--------------|--------------|--------------|-----------|----------|
| 200252 | 3/8" | 1/4" | 910 | 775 | 745 | 725 | 710 | 600 | 450 | Bag of 25 | 60 Bags |
| 200233 | 5/8" | 1/2" | 721 | 612 | 589 | 577 | 564 | 480 | 360 | | 20 Bags |
| 200253 | 3/4" | 5/8" | 631 | 537 | 515 | 505 | 495 | 421 | 315 | | 10 Bags |
| 200234 | 7/8" | 3/4" | 582 | 495 | 474 | 466 | 455 | 387 | 290 | Bag of 10 | |

