

Duct Strap operational temperature is -4F to 185F (-20C to 85C) with a minimum installation temperature of 5F (-15C) per UL 62275.

-OW suffix black Duct Straps are rated for UV exposure and indoor/outdoor use per UL 62275.

Duct Straps are UL 181B-C rated for mechanical fasteners for use with flexible air ducts. This includes testing to ANSI/UL 723 "Test for Surface Burning Characteristics of Building Materials" and UL 2043 "Fire Test for Heat and Visible Smoke Release for Discrete Products and Their Accessories Installed in Air-Handlina Spaces" as well.

These products have been found to be suitable for use in plenums in accordance with the "International Mechanical Code," "Uniform Mechanical Code," and ANSI/NFPA 90A, "Installation of Air-Conditioning and Ventilating Systems."

Usage Recommendations: The cable ties must be stored at room temperature in at least 50% humidity (recommended 80%RH) in a completely sealed polyethylene bag if not being used. In extreme heat and cold, limit the exposure of unused cable ties. If after being exposed to extreme temperatures and/or extreme relative humidities, the cable ties must be allowed to be stored at room temperature and at least 50% humidity (recommended 80%RH) for at least 24 hrs in a sealed bag before being used again.

Recommended for use with tool CTT-703S

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF CAMBRIDGE RESOURCES. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF CAMBRIDGE RESOURCES IS PROHIBITED.

DRAWN UNLESS	name RH Otherwise	DATE 11/08/13 SPECIFIED:	CAMBRIDGE RESOURCES 960 Alabama Ave, Brooklyn, NY 11207 P:718-649-1666 F:718-485-4403					
DIMENSIONS ARE IN INCHES [] DENOTES MILLIMETER  MATERIAL			Duct Straps					
Nylon 6,6 94V-2		SIZE <b>A</b>	DWG. NO. Duct Straps REV B				REV B	
DO NOT SCALE DRAWING			SC	CALE: 1:1	WEIGHT:		SHEET	1 OF 1

3