



Cambridge Part #	Length L	Max Bundle Dia A	Max Bundle Dia B
CTDH8-50	7.87 [200]	1.85 [47]	1.77 [45]
CTDH11-50	11.81 [300]	2.83 [72]	2.76 [70]



PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS
 DRAWING IS THE SOLE PROPERTY OF
CODA RESOURCES, LTD. ANY
 REPRODUCTION IN PART OR AS A WHOLE
 WITHOUT THE WRITTEN PERMISSION OF
CODA RESOURCES IS
 PROHIBITED.

Rated Operating Temperatures:
 -40°F to 185°F (-40°C to 85°C)

Usage Recommendations:

The cable ties must be stored at room temperature in at least 50% humidity (recommended 80%RH) in a completely sealed polyethylene bag if not being used. In extreme heat and cold, limit the exposure of unused cable ties. If after being exposed to extreme temperatures and/or extreme relative humidities, the cable ties must be allowed to be stored at room temperature and at least 50% humidity (recommended 80%RH) for at least 24 hrs in a sealed bag before being used again

NAME	DATE	CAMBRIDGE 960 Alabama Ave, Brooklyn, NY 11207 P:718-649-1666 F:718-485-4403		
DRAWN	RH			
UNLESS OTHERWISE SPECIFIED:		TITLE: Double Headed Cable Tie 50lb Tensile Strength		
DIMENSIONS ARE IN INCHES [] DENOTES MILLIMETER		SIZE A	DWG. NO. CTDH REV A	REV A
MATERIAL Nylon 6,6 FINISH		DO NOT SCALE DRAWING		
		SCALE: 1:1	WEIGHT:	SHEET 1 OF 1