



| Cambridge Part# | Length (L) | Width (W) | Thickness (T) | Max Bundle Dia. |
|-----------------|-------------|------------|---------------|-----------------|
| CTRG6-50 | 5.90 [150] | 0.30 [7.6] | 0.054 [1.37] | 1.40 [35] |
| CTRG8-50 | 7.87 [200] | 0.30 [7.6] | 0.054 [1.37] | 1.97 [50] |
| CTRG10-50 | 9.84 [250] | 0.30 [7.6] | 0.054 [1.37] | 2.60 [66] |
| CTRG12-50 | 11.81 [300] | 0.30 [7.6] | 0.054 [1.37] | 3.15 [80] |
| CTRG14-50 | 14.57 [370] | 0.30 [7.6] | 0.054 [1.37] | 4.00 [102] |

*Please Inquire About Other Sizes Not Listed
 **See Cambridge Catalog for Colors and Packaging Options



PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF **CODA RESOURCES**. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF **CODA RESOURCES** IS PROHIBITED.

Rated Operating Temperatures:
 -40°F to 185°F (-40°C to 85°C)

Usage Recommendations:
 The cable ties must be stored at room temperature in at least 50% humidity (recommended 80%RH) in a completely sealed polyethylene bag if not being used. In extreme heat and cold, limit the exposure of unused cable ties. If after being exposed to extreme temperatures and/or extreme relative humidities, the cable ties must be allowed to be stored at room temperature and at least 50% humidity (recommended 80%RH) for at least 24 hrs in a sealed bag before being used again

| | | | | | |
|----------------------------------------------------|------|----------|---------------------------------------------------------------------------------------|------------|--------------|
| | NAME | DATE | CAMBRIDGE 960 Alabama Ave, Brooklyn, NY 11207 P:718-649-1666 F:718-485-4403 | | |
| DRAWN | RH | 05/12/10 | | | |
| UNLESS OTHERWISE SPECIFIED: | | | TITLE: Cambridge Releasable Cable Ties | | |
| DIMENSIONS ARE IN INCHES [] DENOTES MILLIMETER | | | SIZE | DWG. NO. | REV |
| MATERIAL Nylon 6,6 94V-2 | | | A | CTRG REV A | A |
| FINISH | | | SCALE: 1:1 | | SHEET 1 OF 1 |
| DO NOT SCALE DRAWING | | | | | |