



Cambridge Part#	Length (L)	Width (W)	Thickness (T)	Max Bundle Dia.	Tensile Strength (lbs)	Hole Diameter
CTM4-18	4.33 [110]	0.10 [2.5]	0.04 [1.01]	0.87 [22]	18	0.126 [3.2]
CTM6-40	5.95 [152]	0.14 [3.6]	0.04 [1.01]	1.26 [32]	40	0.165 [4.2]
CTM8-50	7.87 [200]	0.19 [4.8]	0.054 [1.37]	1.97 [50]	50	0.216 [5.5]
CTM11-50	12.20 [310]	0.19 [4.8]	0.054 [1.37]	2.99 [76]	50	0.216 [5.5]
CTM14-50	14.84 [377]	0.19 [4.8]	0.054 [1.37]	4.02 [102]	50	0.216 [5.5]
CTM15-120	14.96 [380]	0.30 [7.6]	0.072 [1.83]	3.86 [98]	120	0.248 [6.3]

*Please Inquire About Other Sizes Not Listed
 **See Cambridge Catalog for Colors and Packaging Options



PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF CODA RESOURCES. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF CODA RESOURCES IS PROHIBITED.

Rated Operating Temperatures:
 -40°F to 185°F (-40°C to 85°C)

Usage Recommendations:
 The cable ties must be stored at room temperature in at least 50% humidity (recommended 80%RH) in a completely sealed polyethylene bag if not being used. In extreme heat and cold, limit the exposure of unused cable ties. If after being exposed to extreme temperatures and/or extreme relative humidities, the cable ties must be allowed to be stored at room temperature and at least 50% humidity (recommended 80%RH) for at least 24 hrs in a sealed bag before being used again

	NAME	DATE	CAMBRIDGE 960 Alabama Ave, Brooklyn, NY 11207 P:718-649-1666 F:718-485-4403		
DRAWN	J Li	10/17/06			
UNLESS OTHERWISE SPECIFIED:			TITLE:		
DIMENSIONS ARE IN INCHES [] DENOTES MILLIMETER			Cambridge Screw Mount Cable Ties		
MATERIAL Nylon 6,6 94V-2			SIZE	DWG. NO.	REV
FINISH			A	CTM Screw Mount REV A	A
DO NOT SCALE DRAWING			SCALE: 1:1	WEIGHT:	SHEET 1 OF 1